

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/050535 A2

- (51) International Patent Classification⁷: B67D
- (21) International Application Number:
PCT/IB2003/005411
- (22) International Filing Date:
26 November 2003 (26.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0227941.2 29 November 2002 (29.11.2002) GB
- (71) Applicant (for all designated States except US): INTER-
BREW S.A. [BE/BE]; Vaarstraat 94, B-3000 Leuven (BE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): WAUTERS, Albert
[BE/BE]; Admiraalhof 24, B-9070 Destelbergen (BE); AN-
DERSON, Ian [GB/GB]; 19 Silver Street, Burwell, Cam-
bridge CB5 0EF (GB).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, GR, GU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


- (84) Designated States (regional): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ALCOHOL BEVERAGE DISPENSING APPARATUS



(57) Abstract: The present invention relates to a conduit for conducting gasified liquid, which has a flow restrictor arranged in in-line relation therewith. The restrictor itself comprises an at least one aperture (although two or more can be used in series), with each such being adapted to pass the gasified liquid flowing through the conduit and across a pressure drop from a higher-pressure upstream side of the aperture to a lower-pressure downstream side of the aperture. The aperture is operable to moderate the rate of change in pressure over a transitional pressure drop to mitigate the formation of localized pressures below a critical pressure at which off-gassing from the carbonated liquid results in substantial foam formation. The conduit may take the form of a dispensing tube for use in dispensing an alcoholic beverage from a keg, the tube having a flexible wall deformable under the influence of a restricting actuator to control the partial collapse of the wall and thereby form the restrictor. The tube or flow diameter downstream of the restrictor only gradually or slowly increases.